

df FINECO2

The firstly-developed FINECO2 has acquired the F1 certification. It guarantees the best stability for the great quality cylinder made by the FINETEC , efficiency, and the convenience of construction. Especially, the FINTEC Gas Agent Calculation Program called "화가-Pro" has solved the problems of the other program therefore, It has been offering the best fire extinguishing efficiency and the stability of installation.

1. Basic Information

agent	CARBON-DIOXIDE(CO2)
design concentration	A Grade surface fire : 34% B Grade surface fire : fire design concentration electronic Installation : 50% deep-seated fire : 75%
SYSTEM	charging pressure : 60kg/cm ² discharge pressure : 21kg/cm ² 이상 fill density : 0.67kg/ℓ agent in piping : 35% 이하
basic condition	purity : 99.5% over(steam)_ No color, No smell water content : weight rate 0.01% and below (-30°F(-34℃)) oil content : weight rate 10ppm and below

2. Specific Feature

- 1) FI certification 02-1 : extinguish Installation SYSTEM certification
- 2) extinguish power : Excellent extinguishing efficiency in the A, B, C Grade fire .
- 3) FINECO2 can possibly simulate as the F1 certified program.
- 4) The improved System components
 - the improved cylinder valves for stability
 - The equivalent length is minimized , the directional valve for the stability and construction.
 - FLEX. HOSE has check-valves within
 - The nuzzle
 - FINECO₂ private use big capacity Cylinder